

# Team 27(ME)/18(ECE): Mars Lander Robot Recharger



*QinetiQ*




Spring Midterm 2

# Team Members / Advisors

- Team Members
  - Itiel Agramonte
  - Dean Gonzalez
  - Lucas Kratofil
  - Tyler Norkus
  - James Whaley
- Advisors / Technical Contacts
  - Dr. Moore – ME Advisor
  - Dr. Arora – ECE Advisor
  - Van Townsend – Technical Point of Contact
  - Michael Solomon – Intellectual Property Point of Contact

# Project Scope

- Get power from the stationary lander to the rovers
- Hydrogen fuel cell bank on board the lander
- Two 12V Lead Acid Batteries onboard the rovers
- Rovers drive up to be refueled
- Station records current charge state
- Fills batteries to 100%




# Fall Semester Accomplishments

- The arm and rover connections were designed according to constraints set forth by sponsor
- Simplicity was very desirable




# Lander Arm




Explode State:EXP00C1(+)

Dean Gonzalez

# Rover Connection




# Electrical System







# Charge Control

- Power Stream PST-BC2424-10 DC-DC
  - 24-32V input
  - Adjustable output current, up to 10 Amps
  - 4 stage charging algorithm
  - Short Circuit/polarity protection



# Four State Charging



# Safety and Ergonomics

- QinetiQ has asked for safety systems to protect workers in the Lab.

## Risk:

- Possibility for shocks/burns to occur if human hand were to be placed on plate
- Possibility for metal tools to short plates creating a sudden large current that could burn out the lander circuit

## Solution:

- First charge stage is current-limited,  $<100\text{mA}$ .
- Diode at the base of the rover connection.
- Fuse in the rover.

# Budget/Procurement

	Cost (in USD) to Prototype as Designed
<b>Prototyping</b>	
<b>TOTAL COST TO PROTOTYPE</b>	1099.84
<b>Testing</b>	
<b>TOTAL COST TO TEST</b>	119.27
<b>SHIPPING AND HANDLING CHARGES</b>	250.00
<b>UNFORESEEN EXPENSES</b>	530.89
<b>GRAND TOTAL</b>	<b>2000.00</b>

- Procurement began in November.
- Final purchase orders have been placed.

# Conclusions / Analysis

- Full arm design completed
  - Simple/Robust/Reliable
  - NASA Approves
- Completed lander and rover connection designs
  - Effective design for the application, efficient, and safe
- Materials selection process
  - Lightweight, within mass constraints of <4kg
  - Low forces/stresses experienced
- Procurement completed (with complications)

# Future Work

- Build final prototype
  - Simulate Lander deck using wood
  - Working prototype of arm
  - Initial deployment successful
  - Test using ATRV-Jr at acceptable angles of approach and elevation angles
- Test circuit (measure efficiency to ensure within requirement of  $>75\%$ )

# References

- [1] [http://www1.eere.energy.gov/hydrogenandfuelcells/fuelcells/fc\\_types.html](http://www1.eere.energy.gov/hydrogenandfuelcells/fuelcells/fc_types.html)
- [2] [http://www.afcenergy.com/technology/advantages\\_of\\_alkali\\_fuel\\_cells.aspx](http://www.afcenergy.com/technology/advantages_of_alkali_fuel_cells.aspx)
- [3] [http://www1.eere.energy.gov/hydrogenandfuelcells/fuelcells/pdfs/fc\\_comparison\\_chart.pdf](http://www1.eere.energy.gov/hydrogenandfuelcells/fuelcells/pdfs/fc_comparison_chart.pdf)
- [4] [http://en.wikipedia.org/wiki/Atmosphere\\_of\\_Mars](http://en.wikipedia.org/wiki/Atmosphere_of_Mars)
- [5] [http://ieeexplore.ieee.org/xpls/abs\\_all.jsp?arnumber=1554624&tag=1](http://ieeexplore.ieee.org/xpls/abs_all.jsp?arnumber=1554624&tag=1)
- [6] <http://www.jameco.com/Jameco/Products/ProdDS/178597.pdf>
- [7] <http://www.space.com/16907-what-is-the-temperature-of-mars.html>
- [8] [http://www.nasa.gov/audience/foreducators/topnav/materials/listbytype/What\\_Is\\_the\\_Temperature.html](http://www.nasa.gov/audience/foreducators/topnav/materials/listbytype/What_Is_the_Temperature.html)
- [9] <http://quest.nasa.gov/aero/planetary/mars.html>
- [10] [http://www.jpl.nasa.gov/news/press\\_kits/MSLLaunch.pdf](http://www.jpl.nasa.gov/news/press_kits/MSLLaunch.pdf)

# Questions, Comments?

