

Dr. Leon VanDommelen, Exam 1, 10/04/18, Question 1

Table of Contents

Initialize	1
My Solution:	1
Additional m-File: Kepler.m	2

IMPORTANT:

- 1) Do not change **anything** in this header! Put the solution to the question completely at the end of the file.
- 2) Since the solution requires a custom function Kepler, put a

```
%% Additional m-File: Kepler.m  
%  
% <include>Kepler.m</include>
```

block behind your main solution. (Copy the above three lines and paste them completely at the end of this file, behind a blank line. For each line, get rid of the first percent and the two spaces behind it.)

Initialize

```
format compact  
more off
```


My Solution:

```
% data for the two cases  
e=0.5;  
M1=pi/4;  
M2=3*pi/4;  
  
% plot curves  
EPlot=linspace(0,pi,100);  
error1Plot=Kepler(EPlot,M1,e);  
error2Plot=Kepler(EPlot,M2,e);  
plot(EPlot,error1Plot,'r',...  
      EPlot,error2Plot,'b')  
grid on  
legend('M = pi/4','M = 3 pi/4')  
  
% find values of E  
M=M1;  
E1=1;  
E2=1.5;  
E=fzero(@(E) Kepler(E,M,e), [E1 E2]);
```

- ① know must form error
- ① write Kepler.m
- ② plot curves
- ② grid
- ② legend
- ⑤ find intervals
- ⑤ fzero call
- ⑤ anonymous function

```
fprintf('For e = %.3f and M = %.5f, E = %.5f (interval [%.3f %.3f]).\n', ...  
      e, M, E, E1, E2)  
M=M2;  
E1=2.5;  
E2=3;  
E=fzero(@(E) Kepler(E,M,e), [E1 E2]);  
fprintf('For e = %.3f and M = %.5f, E = %.5f (interval [%.3f %.3f]).\n', ...  
      e, M, E, E1, E2)
```

For e = 0.500 and M = 0.78540, E = 1.26170 (interval [1.000 1.500]).
For e = 0.500 and M = 2.35619, E = 2.60975 (interval [2.500 3.000]).



Additional m-File: Kepler.m

```
function error = Kepler(E,M,e)  
  
% evaluate the error in the equation  
error=M-E+e*sin(E);  
  
end
```

Dr. Leon VanDommelen, Exam 1, 10/04/18, Question 2

Table of Contents

Initialize	1
My Solution:	1

IMPORTANT:

Do not change **anything** in this header! Put the solution to the question completely at the end of the file.

Initialize

format compact
more off

My Solution:

(5) create data xVals *(5) max error* *(4) plot*
(5) polyfit *(2) fprintf* *(2) symbols, lines, colors*
(5) polyval (Harder) *(3) polyder* *(2) axes*
15 *10* *9*


```
% create noisy data
xVals=linspace(-pi/2,pi/2,50);
rng('default')
fVals=sin(xVals)+0.1*randn(size(xVals));

% create fit
CoefQuintic=polyfit(xVals,fVals,5);

% maximum error at the plot points
xPlot=linspace(-pi/2,pi/2,100);
fQuinticPlot=polyval(CoefQuintic,xPlot);
errQuintic=max(abs(fQuinticPlot-sin(xPlot)));
fprintf('The quintic fit has a maximum error %.2E\n',errQuintic)

% plot
fExactPlot=sin(xPlot);
derfExactPlot=cos(xPlot);
derCoefQuintic=polyder(CoefQuintic);
derfQuinticPlot=polyval(derCoefQuintic,xPlot);
plot(xPlot,fExactPlot,'--k',...
      xVals,fVals,'ok',...
      xPlot,derfExactPlot,'--k',...
      xPlot,fQuinticPlot,'b',...
      xPlot,derfQuinticPlot,'b')
grid on
axis([-pi/2 pi/2 -1.2 1.2])
```

The quintic fit has a maximum error 9.50E-02



Published with MATLAB® R2017b

Dr. Leon VanDommelen, Exam 1, 10/04/18, Question 3

Table of Contents

Initialize	1
My Solution:	1
Additional m-File: ODE.m	2

IMPORTANT:

- 1) Do not change **anything** in this header! Put the solution to the question completely at the end of the file.
- 2) Since the solution requires a custom function ODE, put a

```
%% Additional m-File: ODE.m  
%  
% <include>ODE.m</include>
```

block behind your main solution. (Copy the above three lines and paste them completely at the end of this file, behind a blank line. For each line, get rid of the first percent and the two spaces behind it.)

Initialize


```
format compact  
more off
```

My Solution:

```
[yValues unknownsValues] = ...  
    ode45('ODE', linspace(0,4,100), [0 0 .47]');  
uValues=unknownsValues(:,2);  
plot(uValues,yValues,'b')  
title('Blasius Velocity Profile')  
xlabel('u')  
ylabel('y')
```

*(9) create function ODE
(4) ode45 call, generic
(4) put in initial conditions
(4) put in t-range*

*(5) take u out of unknowns values
(4) plot axes as requested
(3) title, xlabel, ylabel*



Additional m-File: ODE.m

```
function unknownsDerivatives = ODE(y,unknowns)

% take the unknowns out of the vector for readability
p=unknowns(1);
u=unknowns(2);
o=unknowns(3);

% derivatives of the unknowns
dpdy=u;
dudy=o;
dody=-p*o;

% return the derivatives as a *column* vector
unknownsDerivatives=[dpdy dudy dody]';

end
```

Published with MATLAB® R2017b